



United Standard Solar Technology

Green energy for the world


Usst MPPT Solar Charge Controller

MPPT Solar Charge Controller

USCH-30A 12V/24V/36V/48V

Feature :

- 12V/24V/36/48V Auto work, parallel design
- Multi-stage charging optimizes battery performance
- MPPT efficiency >99.5%, Peak conversion efficiency 97.5%
- Compatible with Gel. AGM. Flooded. Sealed lead acid and Lithium battery
- Multi-function LCD+LED display, system information intuitively
- Comprehensive protection
- Excellent Heatsink cooling design, quiet operation
- Comfortable installation and commissioning
- Monitoring your system on line via RS485 communication




Application



United Standard Solar Technology

www.usstenergy.com

Application Diagram



Technical Data

Usst MPPT Solar Charge Controller USCH-30A

Solar System Voltage	12V/24V/36V/48V Auto work
Electrical	
PV Operating Voltage	12V 18~150Vdc
	24V 35~150Vdc
	36V 50~150Vdc
	48V 60~150Vdc
Max. PV input power	12V 400W
	24V 800W
	36V 1300W
	48V 1700W
Rated input current	30A
Rated DC load current	40A
Self consumption	2W
Max.Conversion Efficiency	97.50%
Protection	PV array short circuit, over charging,battery reverse polarity,output short circuit
Battery charging	
Battery Type	Sealed Gel AGM Flooded Lithium Battery
Charge algorithm	3 stage: Bulk, Absorption, Float
Bulk charge voltage	Sealed: 14.4V AGM 14.2V Gel:14.2V Flooded:14.6V User defined:10-15V
Float charge voltage	Sealed/Gel/AGM:13.8V Flooded:13.7V User defined:10-15V
Equalize charge voltage	Sealed 14.6V AGM:14.8V Flooded:14.9V
Load disconnect voltage	10.5V ~12V Adjustable
Low voltage reconnect voltage	12.5V
Temperature compensation	5MV/
Communication	
Communication Port	RS485(Standard) Ethernet RS232 Optional with On line monitoring system
Physical	
Technical data for 12V system at 25℃. twice in 24V system rate. triple in 36V System rate and quaduple in 48V system rate.	
Net weight	3.3kg
Gross weight	4kg
Dimension	220*170*90MM
Cooling	Heatsink cooling
Enclosure	IP45
Environment	
Ambient operating temperature	-25
Storage Temperature	-40
Humidity	5%-95% non-condensing

